

# TELENCO® UPB NG UNIVERSAL POLE BRACKET



The universal pole bracket Telenco® UPB NG is made of aluminum alloy and provides for high mechanical resistance. This new version is compatible with 5/14 and 5/15 cross-arms. Equipped with anti-rotation lugs, the Telenco® UPB NG requires a single bolt for its installation AND to support a cross-arm.

Its unique and patented design was developed to offer an universal pole hardware accessory meeting all mounting applications' needs for wooden, steel or concrete poles.

This pole bracket enables:

- cable unrolling on pulley
- cable dead-ending
- stay wire
- double anchoring
- cross-arm fastening
- angled passageways
- customer connection
- triple anchoring

PN	DESIGNATION	DIMENSIONS		PACKG
91491	UPB NG	138.5 x 100 x 30mm	0.22kg	30 units

## TECHNICAL CHARACTERISTICS

- Material: Aluminum
- Mechanical strength: from 200 to 930daN (depending on anchor points and uses)

## INSTALLATION

- On non-drillable poles (concrete, steel,...):
  - two pole bands equipped with buckles + one 1/12 bolt for fastening the cross-arm
- On pre-drilled poles (steel, concrete,...):
  - one 1/06 pole head bolt

## FEATURES & BENEFITS

- Version equipped with anti-rotation lugs ensuring the stability of cross-arms
- Mounts with one single bolt
- Multi-use product: enables the cross-arm fastening, simple or double anchoring, stay wire,...
- Compact and lightweight model: compatible with wooden, steel or concrete poles.

